

# KLIS265 IP MICROBULLET

## 2MP IR Motorized Bullet Network Camera

KLIS265 IP MICROBULLET is a 2 Megapixel Multiple Streams IP Microbullet Camera supports both H.264/H.265 and MJPEG standard. The H.265 encoder performance is up to 2MP @ 25 fps. With more computing power, it could provide more flexibility for users and system managers. The camera supports WDR function, which can provide better image quality under extreme light contrast scenario or light changing environment.



### FEATURES

- H.265, H.264 Support
- 2MP Resolution
- Motorized Varifocal 2.8~12mm Lens
- True Day & Night
- WDR (ATR-EX)
- 24 IR LEDs for 30m Coverage
- PoE
- IP66
- Smart Codec
- Tampering
- Triple Stream(H.264/H.265, MJPEG)
- Onvif – Genetec Protocol
- Easy Install : Zero Configuration, Discovery, PoE
- Multi User Authority, IP Filtering, HTTPS, SSL
- Cross Web Browsing(IE, Safari, Firefox, Chrome)
- Privacy Masking

# TECHNICAL SPECIFICATIONS

IMAGE		
Lens		Motorized Varifocal 2.8~12mm F1.4
Angle of View		94°(H)~34°(H)
Image Sensor	Type	1/2.9" Sony Exmor CMOS
	Pixels	1984(H)x1125(V)
Min. Illumination		Color : 0.1Lux@F2.1 / BW : 0Lux@F2.1(IR LED On)
Scanning Mode		Progressive Scan
Wide Dynamic Range		Yes
Day and Night Mode		True D/N(Auto, Day, Night)
Noise Reduction		2DNR, 3DNR
Digital Zoom		ROI
Exposure Control		Auto
White Balance Control		Auto, Manual
Back Light Compensation		Yes
Image Effect		Flip, Mirror, Defog
Flicker Free Mode		50Hz, 60Hz
Shutter Speed		Auto(1/10,000~1sec), Manual
IR Illuminator	Quantity	24 IR LEDs
	Angle	90/30°(H)
	Distance	30m
VIDEO/AUDIO		
Compression		H.264(Baseline, Main, High Profile), MJPEG
Bitrate Control		CBR, CVBR
Resolution		1920x1080, 1280x1024, 1280x720/960, 1024x768, 704x480/576, 640x480, 320x240
Frame Rate		Max. 30/25fps(NTSC/PAL)
Streaming		Triple Stream : H.264/H.265x2, MJPEGx1
SYSTEM		
Video Contents Analysis		Tampering
Motion Detection Area		16 Programmable Area(Include Area 8, Exclude Area 8)
Privacy Mask Zone		4 Programmable Zone
Smart Codec ROI		8 Regions
FTP Uploading		MJPEG
Event Notification		E-mail, FTP, Notification Server, XML Notification
Login Authority		Administrator, Operator, Guest
Event Buffering(FTP)		Pre : 30sec, Post : 30sec
Manual Trigger		4 Programmable Trigger
Security		Multi User Authority, IP Filtering, HTTPS, SSL
Network Time Sync		NTP Server, Synchronized Computer, Manual
Software Reset		Restart, Reset, Factory Default
Auto Recovery		Backup, Restore
Remote Upgrade		Web Browsing(IE, Chrome, Safari, Firefox), SmartManager
NETWORK		
Protocol		TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, QoS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Client Software		Web, SmartManager, Client S/W, Mobile S/W
Max. User Connection		Live : 10 Users, Playback : 3 Users
API Support		Open API, Onvif Compliance
Mobile Support		Android, iOS
EXTERNAL IN/OUT		
Video Composite Out		-
Audio		-
Alarm		-
Ethernet		RJ-45(10/100Base-T)
u-SD Card		-
ETC		
Operating Humidity		95% or less(Non-Condensing)
Operating Temperature		-20~+50°C
Power Supply		PoE/12VDC
Power Consumption		145mA(7W)@PoE / 480mA(5.8W)@12VDC
Dimension		81(W)x82(H)x239(D)mm
Net Weight		Approx. 680g
Ingress Protection		IP66
Vandal Proof		IK10 (no glass part)

All specifications subject to change without notice



**Euklis s.r.l.**

Via C. Colombo, 23 - 20090 Trezzano s/N (MI) - Italy  
Tel. (+39) 02.48.40.92.67 - Fax (+39) 02.48.40.92.66 - [www.euklis.it](http://www.euklis.it)