

## KLIS IPCAM-3M

Klis IPCAM-3M supports 3M video and quad streams codec, the camera offers supreme image quality while keeping efficient and valuable network bandwidth for storage management. Possessing line-by-line HDR technology, camera can also have premium performance under extreme low light contrast scenario or fluctuate lighting environment. Furthermore, with smart event function, alarm / motion can be categorized by event types, which makes event management much easier. The camera offers strengthened support for surveillance application that demands consistent precision focus control while high resolution and superior video quality are requisite. In addition, considering that precise focus adjustment can be difficult during installation, the auto back focus mechanism is designed to allow simple control with just one click.



### FEATURES

- Multiple Progressive Scan CMOS Sensor Support 3M Resolution
- Multi-exposure HDR
- Low Latency Live Streaming
- Low Power Consumption on Encoding
- Quad codec support (H.264 Baseline / Main Profile / High Profile / MJPEG)
- Quad Streams Support
- Text Overlay and Privacy Masks
- Smart Event Function : Audio Detection / Motion Detection / Network Failure Detection / Tampering Alarm
- 3D Motion Compensated Noise Reduction (MCTF)
- BNC analog output
- 64GB SDXC SD Card support
- ONVIF – GENETEC Protocol
- RS 485 Support

# TECHNICAL SPECIFICATION

Camera		KLIS IPCAM-3M
Image Sensor		1/2.8" Sony Progressive CMOS
Effective Pixels		3M (2048x1536)
Minimum Illumination		0.04 lux (color) – 0.002 lux (B/W)
Shutter Speed		1 ~ 1/10000 sec.
Operation		
Multiple Languages		English / French / German / Italian / Japanese / Korean / Portuguese / Russian / Simplified Chinese / Spanish / Traditional Chinese
Image Setting	Iris Control	P-iris
	Backlight Compensation	On / Off
	White Balance	AWB / ATW / Manual / One Push
	Noise Reduction	3DNR / 2DNR / ColorNR
	Wide Dynamic Range	Shutter WDR On/Off (120dB)
	Privacy Mask	On / Off
	Privacy Mask Type	Black
	Brightness	Manual
	Exposure	Auto / Manual
	Sharpness	Manual
	Contrast	Manual
	Saturation	Manual
	Hue	Manual
	Digital Zoom	Support
Event Setting	Audio Detection	On / Off
	Motion Detection	On / Off / BySchedule
	Network Failure Detection	By Schedule / On / Off
	Tampering Alarm	On / Off / BySchedule
Audio	Two-way Audio	Line in / Line Out
	Compression	G.711 / G.726 / AAC / LPCM
Network		
Interface		RJ-45, 10/100 Mbps Ethernet
Video Compression		H.264 (MPEG-4 Part 10/AVC) / MJPEG
Video Streaming	Normal Mode	H.264 3M (2048x1536) @25/30 fps + H.264 D1 @25/30fps
	Dual Streams	
	HDR Mode	H.264 1080p @25/30 fps + H.264 D1 @25/30 fps
	Normal Mode	H.264 3M (2048x1536) @25/30 fps + H.264 cif @25/30 fps + H.264 cif @25/30 fps + H.264 cif @25/30 fps
Quad Streams		
	HDR Mode	H.264 1080p @25/30 fps + H.264 cif @25/30 fps + H.264 cif @25/30 fps + H.264 cif @25/30 fps
Video Resolution	H.264	3M (2048x1536) / Full HD 1080P / SXGA / 720P / XGA / SVGA / D1 / VGA / CIF / QVGA
	MJPEG	Full HD 1080P / SXGA / HD 720P / XGA / SVGA / D1 / VGA / CIF
Protocol		ARP, IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF
Security		HTTPS / IP Filter / IEEE 802.1X
Alarm	Input	2 Set
	Output	5V 10kΩ pull up
Event Notification		1 Set Photo Relay Output 300VDC/AC
Micro SD		HTTP / FTP / SMTP
Supported Web Browser		microSDXC 64GB support
User Account		Internet Explorer (6.0+) / Chrome / Firefox / Safari
Password Levels		20
		User and Administrator
Mechanical		
Lens Mounting		CS Mount
LED Indicator		Power / Link / ACT
Connectors	Auto Iris	P-iris
	Alarm	4 Pin Terminal Block, Pitch 3.5 mm
	Power	3pin Terminal Block
	Ethernet	RJ-45
	Analog Video	1.0 Vp-p / 75 Ω, BNC
	Audio	Two-way Audio (Line in / Line out)
	RS-485	D+, D-
General		
Start-up Temperature		-15°C (5° F)
Operating Temperature		-20°C ~ 55°C (-4° ~ 130° F)
Humidity		10% ~ 90%, No Condensation
Dimension		125 x 82 x 52 mm (L x W x H) w/o Lens
Weight		330 g (0.73 lb)
Power Source		PoE / DC 12V / AC 24V
Power Consumption	Operation(802.3af) System	2.55W
	Operation(802.3af) Others:	ICR Switching: +0.5W
Regulatory		CE / FCC / RoHS

Product specification and availability are subject to change without notice.



**Euklis s.r.l.**

Via C. Colombo, 23 - 20090 Trezzano s/N (MI)

Tel. (+39) 02.48.40.92.67 - Fax (+39) 02.48.40.92.66 - www.euklis.it