

# KLIS IP MD-3M-IR-IK10

## Minidome 3 Megapixel IK10

KLIS IP MD-3M-IR-IK10 è una telecamera facile da installare che supporta l'alimentazione PoE per ridurre la complessità dei cablaggi senza sacrificare le prestazioni. Offre la possibilità di utilizzare multipli flussi video in si di compressione diversa (H.264, MPEG4 e MJPEG). Conforme al protocollo ONVIF Profilo S, questo modello è in grado di fornire piena compatibilità con qualsiasi VMS in tutto il mondo, come Omnicast o Security Center. La telecamera è IP66 e IK10 garantendo l'installazione in esterno antivandalo.



### Caratteristiche

- Risoluzione 3M a 25/30fps
- Obiettivo varifocale da 2.8~12mm (disponibile in versione motorizzata opzionale)
- True Day&Night
- D-WDR(ATR-EX)
- Audio In/Out(1/1), allarme In/Out(1/1)
- Scheda Micro SD fino a 128 GB
- Esposizione automatica
- Bilanciamento del bianco automatico
- Triplo Streaming (H.264, MPEG4 e MJPEG)
- Protocollo Onvif – Genetec supportati
- Web Browsing (Internet Explorer, Firefox, Chrome)
- Maschere Privacy
- 36 IR LED
- PoE, 12VDC
- IP66 - IK10

## SPECIFICHE TECNICHE

IMAGE		
Lens	Varifocal 2.8~12mm, F1.4, DC Iris, disponibile in versione motorizzata (-MOT)	
Angle of View	97~37°(H)	
Image Sensor	Type	1/2.8" SONY STARVIS CMOS Sensor
	Pixels	2065(H)x1553(V)
Min. Illumination	Color : 0.1Lux / BW : 0Lux@F1.4, 50IRE	
Scanning Mode	Progressive Scan	
Wide Dynamic Range	D-WDR(72dB)	
Day and Night Mode	True D/N(Auto, Day, Night)	
Noise Reduction	3DNR	
Digital Zoom	16X	
Exposure Control	Auto	
White Balance Control	Auto, Incandescent, Fluorescent, Outdoor	
Back Light Compensation	Yes	
Image Effect	Flip, Mirror, Aisle, Defog, HLC, S-LDC	
Flicker Free Mode	50Hz, 60Hz	
Shutter Speed	Auto(1/10,000~1sec), Manual	
IR Illuminator	Quantity	36 IR LEDs
	Angle	76°(H)
	Distance	Up to 35m
VIDEO/AUDIO		
Compression	H.264(Baseline, Main, High Profile), MJPEG	
Bitrate Control	CVBR, VBR	
Resolution	2048x1536, 1920x1080, 1280x720/1024, 704x480/576, 640x480, 352x240/288, 320x240	
Frame Rate	Max. 25/30fps@3MP	
Streaming	25/30fps(Triple Stream : H.264x2, MJPEGx1)	
Audio Compression	G.711	
Audio Streaming	2 Way	
SYSTEM		
Video Contents Analysis	Tampering, Line Detector, Field Detector	
Motion Detection Area	16 Programmable Area(Include Area 8, Exclude Area 8)	
Privacy Mask Zone	8 Programmable Zone	
FTP Uploading	MJPEG	
Event Notification	E-mail, FTP, Notification Server, XML Notification, AIHM	
Login Authority	Administrator, Operator, Guest	
Event Buffering	FTP	Pre : 30sec, Post : 30sec
	SD Record	Pre : 10sec, Post : 60sec
Manual Trigger	4 Programmable Trigger	
Security	Multi User Authority, IP Filtering, HTTPS, SSL	
Network Time Sync	NTP Server, Synchronized Computer, Manual	
Hardware Factory Reset	Yes	
Auto Recovery	Backup, Restore	
Remote Upgrade	Web Browsing(IE, Chrome, Safari, Firefox), SmartManager	
SD Recording Mode	Event, Continuous	
NETWORK		
Protocol	TCP/IP, UDP, IPv4/v6, HTTP, HTTPS, QoS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Bonjour	
Client Software	Web, SmartManager, Client S/W, Mobile S/W	
Max. User Connection	Live : 10 Users, Playback : 3 Users	
API Support	Open API, Onvif Compliance	
Mobile Support	Android, iOS	
EXTERNAL IN/OUT		
Audio	1 Input, 1 Output(Terminal Block)	
Alarm	1 Input, 1 Output(Terminal Block)	
Ethernet	RJ-45(10/100Base-T)	
u-SD Card	SDHC, SDXC(128GB)	
ETC		
Operating Humidity	0~90%RH(Non-Condensing)	
Operating Temperature	-20~+50°C	
Power Supply	PoE(IEEE802.3af Compliance, Class0), 12VDC	
Power Consumption	120mA(5.7W)@PoE / 450mA(5.4W)@12VDC	
Dimension	146(Ø)x106(H)mm	
Net Weight	Approx. 850g	
Ingress Protection	IP66	
Vandal Proof	IK10	

Specifiche e disponibilità del prodotto sono soggette a modifiche senza preavviso.



**Euklis s.r.l.**  
Via C. Colombo, 23 - 20090 Trezzano s/N (MI)  
Tel. (+39) 02.48.40.92.67 - Fax (+39) 02.48.40.92.66 - [www.euklis.it](http://www.euklis.it)