

KLIS NVR-64

64CH Network Video Recorder

KLIS NVR-64 is a network video recorder supporting video compression H.264 and H.265. It is an ideal recording solution for system integrators and installers applicable from big and medium sized surveillance systems and projects. It is equipped with two gigabit ethernet ports and a redundant power supply.



FEATURES

- Support H.264, H.265 Compression
- 64CH 4K Resolution Camera Recording
- 4K Video Display Out
- 2 gigabit Ethernet
- 8 Bay Removable HDD
- RAID 0, 1, 5, 10 Supported
- Redundant Power Supply
- 2U 19" Rack Mountable
- User Friendly Modern User Interface
- 64CH Realtime Live Display
- 64CH Realtime Playback
- Advanced Search (Time, Event, Thumbnail, Text, Smart, VCA)
- NVR/DVR Remote Control (WARP)
- Data Backup in AVI & MP4
- Text (ATM/POS) Overlay
- Support Third-Party Cameras

TECHNICAL SPECIFICATIONS

VIDEO	
Video Input	64 IP
Video Input Resolution	Up to 8MP
Compression	H.264, H.265
Display Output	1 HDMI
Display Resolution	3840x2160, 1920x1080
Display Speed	1600/1920fps
Display Mode	1/4/9/16/25/30/36/64 Split, Sequence, PIP
RECORDING	
Recording Speed	1600/1920fps@8MP
Max. Recording Throughput	512Mbps
Recording Mode	Continuous, Motion, Alarm, C+M, C+A, M+A, C+M+A, Panic
Pre Alarm	1~5sec
Post Alarm	5sec~1hour
PLAYBACK	
Simultaneous Playback	1/4/9/16/25/30/36/64 Split
Playback Mode	Backward, Forward 2~64x
Search Mode	Time, Event, Thumbnail, Smart (Motion), Text, VCA
STORAGE	
Internal HDD	8 SATA Interface (8 HDD)
RAID	0, 1, 5, 10
Backup	USB
Backup File Format	AVI, H4V, MP4
FUNCTION	
Text in	POS/ATM (VSSI-Pro, ASCII, Network)
User Interface	Mouse, USB/RS485 Keyboard
NETWORK	
Ethernet	2 RJ45 10/100/1000 Base-T
Max. Output Throughput	Unlimited (Guarantee 576Mbps, Support Bandwidth Control)
Remote Monitoring	CMS, Mobile, Web, Dashboard
EXTERNAL IN/OUT	
Audio In	1 RCA, 64 Network
Audio Out	1 RCA, 1 HDMI
Alarm In	4 Input (Terminal Block), 64 Network
Alarm Out	2 Output (Terminal Block)
Serial Port	2 RS485 (Terminal Block)
USB	2 USB2.0, 1 USB3.0
ETC	
Operating Humidity	0~90% RH (Non-Condensing)
Operating Temperature	0~+45°C
Power Supply	110~220VAC, Dual Power
Power Consumption	80W (Include 8HDD)
Dimension(WxHxD)	437.2(W)x88(H)x550(D)mm
Net Weight	TBD

All specifications subject to change without notice



Euklis s.r.l.

Via C. Colombo, 23 - 20090 Trezzano s/N (MI) - Italy
Tel. (+39) 02.48.40.92.67 - Fax (+39) 02.48.40.92.66 - www.euklis.it