

KLIS PROFIBULLET

PROFESSIONAL BULLET IPCAMERA

Professional IP camera with Sony Xarina sensor high performance, with a resolution of 2 megapixels up 4K2K, depending on the model. The Profibullet is a Plug and Play solution for professional applications.

It is the first bullet with illuminators with range up to seventy meters restores power POE. The model 4K is also equipped with cooling fan which comes into operation as the temperature exceeds the set threshold. All models include protocol Onvif and Genetec.

The housing is equipped with a connector IP IP67 for a simple connection from the outside and can be supplied with a prewired cable for those installations where it is required the

passage of cables inside the bracket. Some models include motorized zoom so it is not necessary to open the case. For all models equipped with varifocal lens and for maintenance, the case can be opened easily by pivoting on any of three sides.



The different models are distinguished by the sensor, the lighthouse and the type of lens.

FEATURES

- Ultra Dark Vision Sensor FHD, 3 M o 4K2K
- Shutter WDR up to 96dB (for UDV option)
- Quad Streams Compression- H.264 Baseline / Main / High Profile + MJPEG
- Low Latency Streaming Mode Available
- H.264 BP / MP / HP / SVC and MJPEG Encoding Support
- Professional Outdoor Bullet IP
- IR Led integrated up to 75mt (45°)
- Calibrated front glass – crystal - the best for Megapixel
- Genetec Protocol
- ONVIF Profile S Conformant
- POE+ power supply
- Heater and Fan included and powered by POE+

TECHNICAL SPECIFICATION: KLIS PROFIBULLET-4K-40M - KLIS PROFIBULLET-4K-70M

Euklis Advanced Bullet IP 4K varifocal Megapixel lens 8-80, True Day&Night, Integrated Heater, Illuminator 40/70 meters, Power POE External Connector, Fan

| Camera | | |
|---------------------------|--|--|
| Image Sensor | 1/1.7" Sony Progressive CMOS | |
| Effective Pixels | 8M | |
| Minimum Illumination | 0.05 lux @F1.2 (Color) 0.005 lux @F1.2 (B/W) | |
| Shutter Speed | 1 ~ 1/10000 sec. | |
| Operation | | |
| Multiple Languages | English / French / German / Italian / Japanese / Korean / Portuguese / Russian / Simplified Chinese / Spanish / Traditional Chinese | |
| Backlight Compensation | On / Off (w/ Motion Compensation) | |
| White Balance | Manual / AWB / ATW / One Push | |
| Noise Reduction | 3DNR / 2DNR / ColorNR | |
| Wide Dynamic Range (WDR) | On / Off | |
| Privacy Mask | On / Off | |
| Brightness | Manual | |
| Exposure | Auto / Manual | |
| Sharpness | Manual | |
| Contrast | Manual | |
| Saturation | Manual | |
| Hue | Manual | |
| Digital Zoom | Support | |
| Privacy Mask Type | Color | |
| ICR | Auto / Day / Night / Smart | |
| IR Threshold | Adjustable Levels | |
| Motion Detection | On / Off / By Schedule | |
| Tampering Alarm | On / Off / By Schedule | |
| Network Failure Detection | By Schedule / On / Off | |
| Audio Detection | On / Off | |
| Two-way Audio | Line in / Line Out | |
| Compression | G.711 / G.726 / AAC / LPCM | |
| Bit rate | G.726: 16Kbps/24Kbps/32Kbps/40Kbps, G.711: uLAW(64Kbps)/ALAW(64Kbps), AAC:128Kbps, PCM: 128Kbps/256Kbps/384Kbps/768Kbps | |
| Sampling rate | 8 KHz | |
| Auto Back Focus | Support | |
| Network | | |
| Interface | RJ-45, 1Gbps Ethernet | |
| Video Compression | MJPEG / H.264 (MPEG-4 Part 10/AVC) Baseline / Main Profile / High Profile | |
| Video Streaming | Single | H.264 4K2K (3840x2160) @25/30fps |
| | Dual | H.264 4K2K (3840x2160) @20fps + H.264 1080P @20fps or H.264 1080P @50/60 fps + H.264 1080P @25/30 fps Note: 1 of the 2M or under streamings can be MJPEG |
| | Quad | H.264 1080P @50/60 fps + H.264 SXGA @25/30 fps + H.264 720P @25/30 fps + H.264 D1 @25/30 fps Note: 1 of the 2M or under streamings can be MJPEG |
| | *Five | H.264 1080P @50/60 fps + H.264 SXGA @25/30 fps + H.264 720P @25/30 fps + H.264 D1 @25/30 fps + H.264 D1 @25/30 fps Note: 1 of the 2M or under streamings can be MJPEG |
| Video Resolution | H.264 4K2K (3840 x 2160) / Full HD 1080P / SXGA / 720P / XGA / SVGA / D1 / VGA / CIF / QVGA | |
| Video Windows under ePTZ | MJPEG Full HD 1080P / SXGA / 720P / XGA / SVGA / D1 / VGA / CIF / QVGA | |
| Video Analytic Engine | 4 Edge Embedded (Camera Side) | |
| Protocol | ONVIF | |
| Security | ARP, IPv4/v6, TCP/IP, UDP, RTP, MULTICAST, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, HTTPS / IP Filter / IEEE 802.1X | |
| Alarm | Input | 1 Set 5V 10kΩ pull up |
| | Output | 1 Set Photo Relay Output 300V DC/AC HTTP / FTP / SMTP |
| Event Notification | microSDXC 64GB support | |
| Micro SD | Internet Explorer (6.0+) / Chrome / Firefox / Safari | |
| Supported Web Browser | Supportato | |
| Formato corredoio | Supportato | |
| Focus/Zoom Remoto | Supportato | |
| Mechanical | | |
| Lens Mounting | CS Mount | |
| LED Indicator | Power / Link / ACT | |
| Connectors | Iris Control | DC Iris / P-iris |
| | Alarm | 4 Pin Terminal Block, Pitch 3.5 mm |
| | Power | DC jack or 2pin Terminal Block |
| Connectors | Ethernet | RJ-45 |
| | Analog Video | 1.0 Vp-p / 75 Ω, BNC |
| | Audio | Line in / Line Out |
| | RS 485 | N/A / D+ / D- |
| General | | |
| Protection | IP67 – IK10 (no glass part) | |
| Temperature Operating | -20°C ~ 60°C | |
| Power supply | PoE (IEEE802.3at Compliance) | |
| Power consumption | 25W@ PoE | |
| Portate IR | 60°/40m; 28°/70m | |
| Power Consumption | max 8.5W | |
| Dimension | 506(W)x298(H)x159(D)mm | |
| Net Weight | Approx 3800g | |

Product specification and availability are subject to change without notice.



Euklis s.r.l.
Via C. Colombo, 23 - 20090 Trezzano s/N (MI)
Tel (+39) 02.48.40.92.67 – Fax (+39) 02.48.40.92.66 - www.euklis.it