

KLIS IPCAM - 4K - USB

8MP IP Camera with Advanced Video Analytics and IR Night Vision

High-performance **8MP IP camera** with **HDR** and **IR night vision up to 40 m**.

Supports advanced video analytics for face, license plate, and people recognition, tracking, and smart events. **ONVIF/GENETEC** compatible, Micro SD recording, and weatherproof (**IP66**).

- High-performance **8MP IP camera with HDR**
- **IR night vision up to 40 m**
- **Advanced video analytics:** face, license plate, and people recognition, tracking
- **Smart event support:** motion detection, alarms
- **ONVIF/GENETEC** compatible, Micro SD recording
- **Weatherproof (IP66)**



TECHNICAL SPECIFICATION

Sony 4K		
Image Sensor	Sony 4K 1/1.8" Progressive CMOS	
Effective Pixels	HxV = 3864x2180 (4K)	
Pixel Size	2.0 µm	
Frame Rate (Maximum)	H.265	HDR 4K @30fps + 2M @30fps
	H.264	HDR 4K @30fps + 2M @30fps
	MJPEG	1080p @30fps
Lens		
Minimum Illumination	Color	0.04 lux
	B/W	0.002 lux
Lens	Type	Motorized Lens, P-Iris, F1.5
	Focal Length	3.6-11mm
	Horizontal FOV	115.0° (wide), 47.5° (tele)
	Vertical FOV	61.2° (wide), 27.0° (tele)

Camera	
Day and Night	Automatically removable IR-cut filter
Shutter Time	1~1/10K sec.
HDR	Yes
EIS	No
Zoom	Optical zoom, digital zoom ready by lens type
Image Settings	Color, Brightness, Sharpness, Contrast White Balance, Exposure Control 2DNR, 3DNR, NR by Motion Masking, Text Overlay
Corridor Mode	90°, 180°, 270° rotation
Video Codec	
Compression	H.265/ H.264/ MJPEG
Streaming	Up to 4 individually configurable streams in H.265/H.264/MJPEG Configurable resolution/frame rate/bandwidth LBR/VBR/CBR in H.265/H.264
Audio Codec	
Compression	G.711 / G.726 / AAC / LPCM
Streaming	2 way
Audio Input	Line in
Audio Output	Line out
Network	
Interface	1Gbps Ethernet
Security	User Authentication/HTTPS/IP Filter/IEEE 802.1x
Supported Protocols	ARP, PPPoE, IPv4/v6, ICMP, IGMP, QoS, TCP, UDP, DHCP, UPnP, SNMP, SMTP, RTP, RTSP, HTTP, HTTPS, FTP, NTP, DDNS
Onvif	Profile S / G / Q / T conformant
System Integration	
Event Triggers	External Input, Analytics, Network Failure Detection, Periodical Event, Manual Trigger
Event Actions	External output Activation Video and audio recording to edge storage File Upload : FTP, network share and email Notification : HTTP, FTP, email

Intelligent Video Analytics	
General Analytics	Motion Detection/Tampering/Audio detection
DNN Analytics	Face Detection/Tracking/Recognition LPR Detection/Recognition People Counting Human/Vehicle Classification Object Classification/Recognition

General	
Casing	Metal and Plastic
Power	PoE IEEE802.3af, class 0 , max 12.95 watt DC12V, 15.59 watt AC24V, max 13.31 watt, max 25.08 VA
Connectors	RJ45
	Alarm in x2, Alarm out x1, Terminal Block
	DC12V Terminal Block
	AC 24V Terminal Block
	Audio in 3.5mm Jack Audio out 3.5mm Jack
IR Illumination	Illumination distance: 40m
Storage	Support for microSD/microSDHC/microSDXC card Support for recording to NAS
Operating Conditions	-30°C~55°C without heater -55°C~55°C with heater 10%~90%, No Condensation
Storage Conditions	-20°C~70°C
Approvals	EMC CE / FCC Safety LVD Environment IP66
Dimensions	Ø92x224.6 mm
Weight	780 g

All specifications subject to change without notice



Euklis s.r.l.

Viale Leonardo da Vinci 43 - 20090 Trezzano sul Naviglio (MI)
Tel. (+39) 02.48.40.92.67 - www.euklis.it