

KLIS IPCAM-Lite-5M

IR Bullet, built-in POE, 2.8-12mm Motorized Lens



Camera Model	
Image Sensor	501AI
DSP	GK7205V300
Effect Pixel	2880(H)x1620(V)
Scan Mode	Line by line Scan
Electronic shutter	1/25s~1/10000s; Automatic Adjustment
Min Illumination	Color 0.6Lux@F1.2; white&black 0.08Lux@F1.2; 0Lux when IR on
S/N Ratio	≥50dB (AGC OFF)
Day and night switch mode	ICR, Auto / External / Manual / Fixed time control
WDR	>80dB WDR
Digital Noise Reduction	3 DNR
Video Parameters	
Video compression	H.265/ H264
Video resolution	Main stream 2880*1620@20fps,2560*1440/2304*1296/1080P@30fps Sub stream 704*576/640*480 @30fps
Video Bit rate	32Kbps-16Mbps
Image settings	Supports Brightness, Contrast, Saturation, Sharpness, White Balance; AWB, AGC, AE (Automatic Exposure Control); Supports privacy area occlusion; OSD overlay; Image rotation: Normal 90 ° / 270 °; Defog
Peripheral Interface	
Audio / Talkback input	1 CH audio MIC input / linear input
Audio Output	1 CH audio output
POE	Built-in POE
Network Parameters	
Network Interface	10M/100M adaptive Ethernet port
Network Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, UPNP, Websocket, HTTP, SSL, GB2818
Access Standard	Support the latest ONVIF2.42 / GB28181 / SDK
Number of Client Visits	Support 8 users login at the same time
APP	iPhone, iPad, Android

General Parameters	
Housing	IR Bullet V52E
Waterproof rate	IP66
Lens	2.8-12mm Motorized Lens
IR LED	4pcs IR LED
IR range	50M
Power Supply	DC 12V
Power consumption	7.2W(MAX)
Size	94mm(W)x80mm(H)x152mm(L)
Operation temperature	-20°C~50°C



Euklis s.r.l.

Via C. Colombo, 23 - 20090 Trezzano s/N (MI)

Tel. (+39) 02.48.40.92.67 - Fax (+39) 02.48.40.92.66 - www.euklis.it