

# KLIS MD-4M-ROFv2

Vandal dome, WDR 120dB, 2.8-12mm Motorized Lens, built-in POE



<b>Camera Model</b>	
Image Sensor	Sony IMX347
DSP	GK7205V300
Effect Pixel	2712(H)x1538(V)
Scan Mode	Line by line Scan
Electronic shutter	1/25s~1/10000s; Automatic Adjustment
Min Illumination	Color <a href="#">0.01Lux@F1.2</a> (AGC ON); 0Lux when IR on
S/N Ratio	≥50dB (AGC OFF)
Day and night switch mode	ICR, Auto / External / Manual / Fixed time control
WDR	WDR 120dB
Digital Noise Reduction	3 DNR
<b>Video Parameters</b>	
Video compression	H.265+/ H.265/ H264
Video resolution	Main stream 2688*1520/2560*1440@25fps, 1080P@30fps Sub stream 704*576/640*480 @30fps
Video Bit rate	32Kbps-16Mbps
Image settings	Supports Brightness, Contrast, Saturation, Sharpness, White Balance; AWB, AGC, AE (Automatic Exposure Control); Supports privacy area occlusion; OSD overlay; Image rotation: Normal 90 ° / 270 °; Defog
<b>Peripheral Interface</b>	
Audio / Talkback input	1 CH audio MIC input / linear input
Audio Output	1 CH audio output
POE	Built-in POE
<b>Network Parameters</b>	
Network Interface	10M/100M adaptive Ethernet port
Network Protocol	HTTP, HTTPS, TCP/IP, UDP, RTP, FTP, RTCP, RTSP, NTP, DHCP, DNS, DDNS, SNMP, SSL/TLS, WebSocket, UPNP, PPPOE, ONVIF
Access Standard	Support the latest ONVIF2.42 / GB28181 / SDK
Number of Client Visits	Support 8 users login at the same time
APP	iPhone, iPad, Android

General Parameters	
Housing	Vandal proof dome DV19
Waterproof rate	IP68
Lens	2.8-12mm Motorized Lens
IR LED	36pcs $\phi$ 5mm IR LED
IR range	30-35M
Power Supply	DC 12V
Power consumption	5.2W(MAX)
Size	$\phi$ 150x123(H) mm
Operation temperature	-20°C ~ 50°C



**Euklis s.r.l.**

Via C. Colombo, 23 - 20090 Trezzano s/N (MI)

Tel. (+39) 02.48.40.92.67 - Fax (+39) 02.48.40.92.66 - [www.euklis.it](http://www.euklis.it)