

## KLIS IPCAM50-LITE 5-50

**IR Bullet, built-in POE, 50 fps, 5-50mm Motorized Lens**

**IP camera** with **501AI sensor** up to 2880×1620, **WDR >80 dB**, Day/Night ICR and 3D noise reduction.

Supports H.265/H.264, **built-in PoE**, two-way audio, and multi-user management. **ONVIF** compatible and controllable via iOS/Android apps.



# TECHNICAL SPECIFICATIONS

<b>Camera Model</b>	
Image Sensor	501AI
DSP	GK7205V300
Effect Pixel	2880(H)x1620(V)
Scan Mode	Line by line Scan
Electronic shutter	1/25s~1/10000s; Automatic Adjustment
Min Illumination	Color 0.6Lux@F1.2; white&black 0.08Lux@F1.2; 0Lux when IR on
S/N Ratio	≥50dB (AGC OFF)
Day and night switch mode	ICR, Auto / External / Manual / Fixed time control
WDR	> 80dB WDR
Digital Noise Reduction	3 DNR
<b>Video Parameters</b>	
Video compression	H.265/ H264
Video resolution	Main stream 2880*1620@20fps,2560*1440/2304*1296/1080P@50fps Sub stream 704*576/640*480 @30fps
Video Bit rate	32Kbps-16Mbps
Image settings	Supports Brightness, Contrast, Saturation, Sharpness, White Balance; AWB, AGC, AE (Automatic Exposure Control); Supports privacy area occlusion; OSD overlay; Image rotation: Normal 90 ° / 270 °; Defog
<b>Peripheral Interface</b>	
Audio / Talkback input	1 CH audio MIC input / linear input
Audio Output	1 CH audio output
POE	Built-in POE
<b>Network Parameters</b>	
Network Interface	10M/100M adaptive Ethernet port
Network Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, UPNP, Websocket, HTTP, SSL, GB2818
Access Standard	Support the latest ONVIF2.42 / GB28181 / SDK
Number of Client Visits	Support 8 users login at the same time
APP	iPhone, iPad, Android